

Marshall Space Flight Center and the open-source radar software revolution



Timothy J. Lang

Brenda Dolan, Brody Fuchs, Paul Hein, Elizabeth Thompson



Scott Collis, Jonathan Helmus







Acknowledgments

Jason Burks, Steve Nesbitt, George Priftis, Brent Roberts Funding: NASA, DARPA, USDOJ

Background

My radar software history ...

Graduate School – RDSS, Reorder, SPRINT, Fortran, and pltgks

Research Scientist – IDL, solo, Reorder, SPRINT

NASA Civil Servant (2012) – Stick with IDL or go Python?

NASA Marshall's Lightning Group is mostly an IDL shop

But folks are receptive to Python and some want to learn!

I made the switch in early 2014

MSFC Science Goals

1. Understand lightning production in extreme weather events – *GLM*, *ISS-LIS*

2. Validate precipitation estimates from space – GPM

3. Study how well scatterometers characterize convective variability – *RapidScat, CYGNSS*

Open-source radar software, powered by Python, plays a prominent role in all of these tasks!







Marshall MRMS Mosaic Python Toolkit (MMM-Py)

https://github.com/nasa/MMM-Py

<u>Goal</u>

Simplify the ingest, analysis, and display of NOAA MRMS 3D radar reflectivity mosaics in a Python environment

- Can read any format MRMS, from 2009 onward
- Easy tile merging and domain subsetting
- Customizable plotting methods
- Save custom mosaics to file
- Demonstration Jupyter notebooks available



Python Turbulence Detection Algorithm (PyTDA)

https://github.com/nasa/PyTDA

<u>Goal</u>

Estimate eddy dissipation rate (EDR) from arbitrary Doppler radar sweep or volume

- Module contains independent functions for processing
- Works seamlessly with Py-ART Radar object
- NTDA-like filtering and quality control of data if desired
- Uses sklearn trees, NumPy function broadcasting, and some Cython to allow near real-time use on a laptop



Single Doppler Retrieval Toolkit (SingleDop)

https://github.com/nasa/SingleDop

<u>Goal</u>

Estimate low-level 2D winds from single Doppler radar

- Xu et al. (2006) method
- Works with real or simulated radar data
- Background field can be specified or determined via VAD
- Uses Py-ART for data input and display
- Output gridded analyses to Python-readable binary (pickle) or netCDF (xray)
- Contour, vector, and mixed multi-panel plots supported



Colorado State University Radar Tools (CSU_RadarTools)

https://github.com/CSU-Radarmet/CSU_RadarTools



<u>Goal</u>

Provide routine polarimetric radar analysis and QC tools originally developed/used at CSU

- Independent of any other software framework
- Works with ndarrays or scalars
- CSU Fuzzy-Logic Hydrometeor ID (X, C, S-band)
- CSU Blended Rainfall Calculations
- CSU Ice and Liquid Water Mass calculations
- CSU Drop-Size Distribution calculations
- CSU KDP calculations (FIR based)
- Miscellaneous QC (insect filter, despeckling, etc.)
- Each works as importable sub-module
- Thorough demo notebook available, shows how to use with SkewT and Py-ART.



Python Interface to Dual-Pol Radar Algorithms (DualPol)

https://github.com/nasa/DualPol

<u>Goal</u>

Simple workflow for merging CSU_RadarTools with Py-ART

In [5]: print retrieve.radar.fields.keys()

[u'DC', u'DZ', 'FH', u'FL', u'HD', u'PF', u'PH', u'RH', 'method', 'NW', u'AD', u'ZD', u'AH', 'rain', u'ZC', u'VR', u'KD', u'SR', 'MI', 'MU', 'MW', 'D0']

In [11]: display = pyart.graph.RadarDisplay(retrieve.radar) swp = 0 $\lim = [-80, 80]$ fig = plt.figure(figsize=(16, 14)) ax1 = fig.add subplot(221) display.plot ppi('ZC', swp, vmin=0, vmax=70, cmap='gist ncar') display.cbs[0].ax.set ylabel('Reflectivity (dBZ)') display.set limits(xlim=lim, ylim=lim) ax2 = fig.add subplot(222) hidcolor = dualpol.HidColors() display.plot ppi('FH', swp, vmin=0, vmax=10, cmap=hidcolor.cmaphid) display.cbs[1] = hidcolor.adjust_fhc_colorbar_for_pyart(display.cbs[1]) display.set_limits(xlim=lim, ylim=lim) ax3 = fig.add subplot(223) display.plot_ppi('rain', swp, vmin=0, vmax=150, cmap='GnBu') display.set limits(xlim=lim, ylim=lim) ax4 = fig.add subplot(224)display.plot ppi('method', swp, vmin=0, vmax=5, cmap=hidcolor.cmapmeth) display.cbs[3] = hidcolor.adjust meth colorbar for pyart(display.cbs[3]) display.set_limits(xlim=lim, ylim=lim) plt.tight_layout()

- "One-line" implementation for QC, dual-pol retrievals, and integrating results within Py-ART radar object
- Class that simplifies display of HID & rain method colorbars



Python Polarimetric Radar Beam Blockage Calculation (PyBlock)

https://github.com/nasa/PyBlock

<u>Goal</u>

Calculate beam blockage and estimate corrections needed for polarimetric radar data

- KDP Method from Lang et al. (2009)
- Fully Self-Consistent Method from Giangrande and Ryzhkov (2005)
- Interfaces w/ DualPol, Py-ART, CSU_RadarTools
- Process one volume or an entire field campaign's worth of radar volumes
- Output results to image or file
- Demonstration notebook





Other Collaborations

Py-ART Contributions

- Color blindness friendlier rainbow color table
- NOXP radar data reader
- Automated dealiasing testing (Poster session #3 today)





ARTview Contributions

- Minor feature additions
- Code cleanup/bug fixes
- Testing and evaluation





Putting it all together ...

MMM-Py combined with inhouse Python modules that merge MRMS and Lightning Mapping Array (LMA) data to study storms that produce large charge moment change lightning and/or sprites







- Colorado sprite-producing storm (2012)
- MRMS w/ animated Colorado LMA sources

- El Reno storm (2013)
- Tornadic Stage
- MRMS w/ Oklahoma LMA source densities

Putting it all together ...

IPHEx Field Campaign Data Fusion in support of GPM GV

Radars

Mixture of research and ops: NPOL, NOXP, KCAE, KGSP, KHTX, KMRX, KRAX, KFFC

Tasks

- Py-ART to ingest and merge radar volumes onto common grid
- DualPol to compute rainfall and DSD parameters
- CSU RadarTools to mask insect echoes & high differential phase texture, and despeckle remainder



-60-40

80

100 120 140

-60-40

> 100 120

-60

80

100 120

-40

-20

80

-20

-20

140

Putting it all together ...

Exploring the best ways to compare scatterometers to ground-based Doppler radars

<u>Tasks</u>

- Pydap to ingest RapidScat data via OPeNDAP
- Py-ART to ingest radar data and dealias velocity
- SingleDop to perform 2D lowlevel wind retrievals
- Also: DualPol, CSU_RadarTools



Summary

Six Radar Modules

- 1. MMM-Py
- 2. PyTDA
- 3. SingleDop
- 4. CSU_RadarTools
- 5. DualPol
- 6. PyBlock

Open source, play nice with Py-ART, support Python 3, & are available on GitHub right now (nasa & CSU-Radarmet)

Contact Info: timothy.j.lang@nasa.gov



Timothy Lang @tjlang

Just completed a preliminary case study using Python 3 @Py_ART, ARTview (zenodo.org/record/27358#....), and SingleDop (github.com/nasa/SingleDop)

8/11/15, 10:53 AM

+ PyAMPR!



The Future

Major coding done for now, but some possible ideas for directions to go:

- Merge into MSFC_RadarTools?
- Integration of components within Py-ART or wradlib?
- Make part of some future scikits-radar?
- NASA airborne radar module or interface?

But for now ... http://code.nasa.gov takeover!

