# DATA AND OPERATIONAL PROCESSING FOR NASA'S GPM GROUND VALIDATION PROGRAM

# Jason L. Pippitt<sup>1,3</sup>, David B. Wolff<sup>2</sup>, Walter Petersen<sup>2</sup>, David A. Marks<sup>2,3</sup>

1 NASA Goddard Space Flight Center, Greenbelt, Maryland

2 NASA Wallops Flight Facility, Wallops Island, Virginia 3 Science Systems & Applications, Inc, Lanham, Maryland

> AMS 37th Conference on Radar Meteorology Norman, OK September 14-18 2015



# <u>Introduction</u>

The Global Precipitation Measurement (GPM) Mission satellite and international mission led by NASA and JAXA was launched from Tanegashima, Japan on February 27, 2014. For validation support, an extensive network currently consisting of 78 dual-polarimetric weather radars in different meteorological regimes were selected by the GPM GV (ground validation) program to identify biases between ground observations and satellite retrievals, to assess the physical basis for uncertainties, and to improve both ground and space-based retrievals of precipitation.

#### GPM-GV Radar Sites




Fig. 1. Northern hemisphere GPM-GV radar sites. A majority of the radars were selected from the eastern United States to coincide geographically with products from the NOAA/NSSL ground-based National Mosaic and Multi-Radar Multi-sensor Quantitative Precipitation Estimation (NMQ/MRMS).





Fig. 2. Through an international partnership with Brazil, nine S-band radars from the Center for Monitoring and Alerts of Natural Disasters (CEMADEN) network are included in the GPM GV network.

Fig. 3. Flowchart of the GPM GV operating procedure for data acquisition, operational processing, product generation, and data distribution.



# **Data Acquisition**

Radar Type	# of Sites	Acquisition Method
WSR-88D	66	Data are acquired in near real time via Education and Research Consortium (ERC) NEXRAD local data manger (LDM) stream.
CEMADEN	9	Data are acquired through file transfer protocol (FTP) in near real time.
KPOL	1	Provided daily via secure copy (SCP) by Atmospheric Technology Services Company (ATSC).
NPOL	1	NPOL data that correspond with a GPM overpass are obtained in near real time in full-resolution. NPOL full-resolution data sets are retrieved at the radar site on portable hard drives and transported to NASA's Wallops Flight Facility (WFF) where the data are archived.
CHILL	1	Colorado State University (CSU) provides CHILL data from GPM overpasses via FTP on a case-by-case basis.

Table 1. The majority of the radar data retrieval process has been automated through the use of programs and scripts. Radar type, number of sites, and data acquisition methods are shown.

#### **Additional Data Retrieval**

- GPM satellite coincidence files are retrieved from the NASA Precipitation Processing System (PPS) and used to identify overpass details specific to each radar.
- Hourly model soundings are obtained from NOAA and assist in identifying the melting layer and ice crystals.

#### **Operational Processing**

## **Quality Control**

• Quality control (QC) is applied to the radar data using the NASA developed Dual Polarimetric Quality Control (DPQC) algorithm (Pippitt et. al 2013).

#### **Calibration**

• Calibration adjustments are determined via the Relative Calibration Adjustment (RCA) technique (Silberstein et al. 2008; Wolff et al. 2015), self-consistency of polarimetric variables, and vertical profile (birdbath) scans.

#### **Specific Differential Phase**

• Original specific differential phase (K<sub>dp</sub>) is replaced with the calculated estimate derived from Wang and Chandrasekar (2009).

# **Product Generation**

## **Rain Rate Estimates**

- Method 1: a polarimetrically tuned Z-R algorithm that adjusts for drop oscillations (PolZR Bringi et al. 2004). • Method 2: a hydrometeor identification approach referred to as the Dual-Polarization Radar Operational
- Processing System (DROPS2.0 Chen et al. 2015).

#### **Drop Size Distribution Retrievals**

 Median drop diameter (D₀), normalized intercept parameter (N₀), mas weighted mean diameter (D<sub>m</sub>) and the associated normalized interce parameter (N<sub>w</sub>, but referred to in the data files as N<sub>2</sub>) fields are retrieve using polarimetrically tuned regressions via T-matrix simulations fro disdrometer data collected in a wide variety of regimes (Jensen et


/drometeor	Classification	

· The Colorado State University (CSU) warm season Hydrometer Identification (HID) algorithm is used to generate a detailed hydrometeor classification (Dolan et al. 2013).

ISS	DZ	Drizzle		
ept	RN	Rain Ice Crystals		
ed	CR			
om al.	DS	Dry Snow		
	WS	Wet Snow		
	VI	Vertical Ice		
	LDG	Low-density Graupel		
	HDG	High-density Graupel		
eor	HA	Hail		
led	BD/MH	Big Drops/Melting Hail		
	Table 2. HID c	ategories.		


•	Description	Field Name	Description
	Uncorrected Reflectivity	VR	Radial Velocity
	Corrected Reflectivity	FH	Hydrometeor Identification (HID)
	Co-polar Cross Correlation $(\rho_{hv})$	D0	Median Volume Diameter
	Differential Reflectivity (Z <sub>dr</sub> )	DM	Mass Weighted Mean Diameter
	Differential Phase (Φ <sub>dp</sub> )	NW	Normalized Intercept Parameter
	Specific Differential Phase (K <sub>dp</sub> )	N2	Normalized Intercept Parameter
	Spectrum Width	RR	DROPS2 Rain Rate
	Signal Quality Index	RP	PolZR Rain Rate


Table 3. The full complement of products generated and stored as fields in UF format radar data files.



A convective event that occurred at NPOL on 21 June 2015, will be used as an example for GPM GV rainfall products.

(a) corrected reflectivity (CZ), (b) PolZR (RP), and (c) DROPS2.0 (RR). Both approaches identify rain rates greater than 75 mm hr-1 within the convective cells. The DROPS2.0 method appears visually cleaner than the other method. Range rings are at 50 km intervals.





**Hydrometeor Classification** 

median drop diameter diameter (DM), (c) the normalized intercept parameter (NW), and (d) the D<sub>m</sub> associated normalized intercept parameter (N2).

# NPOL1 21 Jul 2015 17:39:24 UTC RHI FH Az: 179.0

from KDOX on 15 2015 (a) **February** reflectivity Range rings are at 50 km intervals.

A mixed phase case

A convective cell case from NPOL on 21 July 2015 (c) corrected reflectivity (CZ) and Hydrometeor Identification (FH).

#### **Data Distribution**

GPM VN overpass and select full data set sites are hosted on public FTP and can be found through the following

#### http://gpm-gv.gsfc.nasa.gov/Radar/

GPM VN visualization tools that enable users to visualize the corresponding data measured space-based Precipitation Radar (PR) and measurements collected by ground radars, can be found via:

## http://opensource.gsfc.nasa.gov/projects/GPMV/index.php

Data requests and questions can be sent to: jason.l.pippitt@nasa.gov

# **Summary**

GPM GV has established an data processing suite using current network of 78 weather radars located in different meteorological regimes to identify errors between ground observations and GPM satellite retrievals, understand the physical basis of uncertainties, and improve both space and ground-based precipitation estimation. GPM GV has automated numerous processing procedures to streamline data flow to the community. Raw data are acquired for all sites and archived locally. Operational processing consisting of quality control calibration, and calculation of specific differential phase i performed prior to rain rate, hydrometeor identification, and DSD retrievals. The final data are in UF format and available to the community through FTP. The resulting data is a key element in bridging the space and time gap between satellite

observations and in-situ surface instrumentation such as rair

gauges and disdrometers.

# <u>References</u>

Bringi V. N., T. Tang, and V. Chandrasekar, 2004: Evaluation of a new polarimetrically based Z-F Chen, H., V. Chandrasekar, R. Bechini, 2015: An Improved Dual-Polarization Radar Rainfall Algorith (DROPS2.0): Application in NASA IFloodS Field Campaign. Journal of Hydrometeorology, (to be

Dolan B., S. A. Rutledge, S. Lim, V. Chandrasekar and M. Thurai, 2013: A robust C-band Appl. Met. And Clim..52, 2162-2186.

Jensen, M. P., and co-authors, 2010: Mid-latitude Continental Convective Clouds Experiment (MC3E). U.S. DOE/SC-ARM/10-004.

Precipitation Measurement (GPM) mission ground validation program. 36th AMS Conference of Radar Meteorology, Breckenridge, CO, September 16-20, 2013.

Pippitt, J. L., D. A. Marks, and D. B. Wolff, 2013: Dual-polarimetric quality control for NASA's Global

Silberstein, D. S., D. B. Wolff, D. A. Marks, D. Atlas and J. L. Pippitt, 2008: Ground Clutter as a Monitor

of Radar Stability at Kwajalein, RMI. J. Atmos. Ocean. Tech., 25, 1492-1505. Wang, Y., and V. Chandrasekar, 2009: Algorithm for Estimation of the Specific Differential Phase. Atmos. Oceanic Technol., 26, 2565-2578. doi: http://dx.doi.org/10.1175/2009JTECHA1358.1

Wolff D. B., D. A. Marks and W. A. Petersen: 2015: General Application of the Relative J. Atmos. Oceanic Technol., 32, 496-506. doi: http://dx.doi.org/10.1175/JTECH-D-13-00185.1