INTEGRATING WIND PROFILING RADARS AND RADIOSONDE OBSERVATIONS WITH MODEL POINT DATA TO DEVELOP A DECISION SUPPORT TOOL TO ASSESS UPPER-LEVEL WINDS FOR SPACE LAUNCH

William H. Bauman III * NASA Applied Meteorology Unit / ENSCO, Inc. / Cape Canaveral Air Force Station, Florida

Clay Flinn USAF 45th Weather Squadron / Patrick Air Force Base, Florida

1. INTRODUCTION

On the day of launch, the 45th Weather Squadron (45 WS) Launch Weather Officers (LWOs) monitor the upper-level winds for their launch customers. During launch operations, the payload/launch team sometimes asks the LWOs if they expect the upper-level winds to change during the countdown. The LWOs used numerical weather prediction model point forecasts to provide the information, but did not have the capability to quickly retrieve or adequately display the upper-level observations and compare them directly in the same display to the model point forecasts to help them determine which model performed the best. The LWOs requested the Applied Meteorology Unit (AMU) develop a graphical user interface (GUI) that will plot upper-level wind speed and direction observations from the Cape Canaveral Air Force Station (CCAFS) Automated Meteorological Profiling System (AMPS) rawinsondes with point forecast wind profiles from the National Centers for Environmental Prediction (NCEP) North American Mesoscale (NAM), Rapid Refresh (RAP) and Global Forecast System (GFS) models to assess the performance of these models. The AMU suggested adding observations from the NASA 50 MHz wind profiler and one of the US Air Force 915 MHz wind profilers, both located near the Kennedy Space Center (KSC) Shuttle Landing Facility, to supplement the AMPS observations with more frequent upper-level profiles. Figure 1 shows a map of KSC/CCAFS with the locations of the observation sites and the model point forecasts.

2. DATA

The goal of this work was to build a GUI that would allow the LWOs to compare model wind profile output to observed wind profiles closest in time to the 0-hour model forecasts. This permits them to determine which model has the best performance, i.e. to initialize the models. Their requirement is to display model forecasts in 3-hour intervals from the current time through 12 hours.

The AMU reviewed the availability of the observational and model data in the 45 WS Meteorological Interactive Data Display System (MIDDS). They determined MIDDS could not be used as

the data ingest and display for this work because the model point data is not ingested by the AMU MIDDS server. Therefore, Microsoft Excel was considered for downloading, ingesting, formatting and displaying the data. The observational data was available from NASA at the KSC Spaceport Weather Archive website (http://kscwxarchive.ksc.nasa.gov/), which consists of all locally collected weather observations at KSC and CCAFS. The best source for model forecast point data for CCAFS (XMR) was available from the Iowa State Weather Archive Server University website (http://mtarchive.geol.iastate.edu). After discussing this with the 45 WS, all agreed that the AMU would develop an Excel GUI that would ingest data from the Spaceport Weather Data Archive and Iowa State University Weather Archive Server with scripts developed using Visual Basic for Applications (VBA) in Excel.



Figure 1. Map of KSC/CCAFS showing locations of the observations from the 50 MHz and 915 MHz profilers at KSC and AMPS at CCAFS. The location of the model point data forecasts is shown at CCAFS.

2.1 Data Acquisition

One challenge with using near real-time data in Excel was to ensure the latest available model data was being acquired and that it was time-matched to the observations. NCEP runs the RAP model every hour and the NAM and GFS models every six hours at 0000, 0600, 1200, and 1800 UTC. Each model produces forecasts at least 12 hours beyond the initial time. The RAP and NAM models output forecasts at 1-hour intervals while the GFS model outputs forecasts at 3-hour intervals. Since each model has a different run

12.5

^{*}*Corresponding author address:* William H. Bauman III, ENSCO, Inc., 1980 N. Atlantic Ave, Suite 830, Cocoa Beach, FL 32931; e-mail: <u>bauman.bill@ensco.com</u>

time to complete the entire forecast cycle, the AMU conducted tests regarding the data availability of the files on the Iowa State server to determine how long after model initialization time the files were ready for download. The conclusion was that the RAP model forecasts are available from the Iowa State server about 1 hour 45 minutes after each hour, the NAM model forecasts are available about 3.5 hours after each initialization time, and the GFS model forecasts are available about 5 hours after each initialization time.

Acquiring observational files from the Spaceport Weather Data Archive website presented two significant challenges for real-time data access. First, the website only acquires observational data once per hour from MIDDS via a dial-up modem. This presents a potential problem with the AMPS observations because a sounding may only be partially complete when the files are acquired from MIDDS resulting in an incomplete sounding profile on the website. The VBA script that processes the observational data will download and process an incomplete AMPS file, which means the height of the wind speed and direction profile will be limited to the height the radiosonde obtained when the file was acquired from MIDDS. In these instances, the LWO will have to wait one hour for the complete AMPS profile to be available for download. Second, there are intermittent times when a file exists but contains no data. Because the file exists on the server, the VBA script will download the file but will not be able to process it.

2.2 Data Processing

Before the data files are retrieved, several scripts are run to determine the current UTC time to ensure the latest model data is downloaded for processing. All time conversions used in the VBA scripts are based on the local time of the user's computer. However, before converting local time to UTC, a check was needed to determine if the current date was within Standard Time (ST) or Daylight Saving Time (DST). This turned out to be a complicated programming effort in VBA, so the AMU researched and downloaded an Excel DST module from Pearson Software Consulting, LLC (http://www.cpearson.com/EXCEL/DaylightSavings.htm) to do this calculation. To make use of this module, the AMU used the Excel built-in function "=NOW ()" to obtain the local time from the user's computer. Next, the DST module is called to determine whether local time is in ST or DST using the function "=IsDateWithinDST()". Finally, to determine the correct UTC, the VBA code adds 5 hours to local time during ST or 4 hours during DST. The UTC time is saved in the Excel GUI and accessed by each script that needs to determine which model data and observations to download. The AMU wrote a VBA script to automatically run the time calculation when the GUI is started. In Excel VBA, naming a macro "Auto-Open" will automatically run all of the code within that macro each time the macro-enabled Excel file is opened.

The LWOs requested using the observations for two applications. First, they want to use them to initialize the models 0-hour forecasts by comparing the observations to each model and determine which model is performing the best. Second, they want to use them to show the launch team how the upper-level winds are forecast to change by displaying the model forecast valid at or near the same time of the most recent observation plus the model forecasts for the next 0-12 hours.

2.2.1. Model Initialization

For the LWOs to initialize the models against the observations based on UTC, a VBA script retrieves the latest available model runs by issuing a File Transfer Protocol (FTP) command to download the observations closest to the model time. Since the observations will be compared to the model 0-hour forecasts, the observations should time-match each model's start time as close as possible. The AMU developed VBA scripts to download, ingest and format the profiler and AMPS observations from the Spaceport Weather Data Archive server. The data files on the server are in American Standard Code for Information Interchange (ASCII) format and are ingested into Excel as a text file. After downloading and ingesting the data files, the VBA code removes all unneeded parameters and reformats the data to prepare it for creating charts. A 50 MHz profiler data file as ingested into Excel is shown in Figure 2a and the reformatted data is shown in Figure 2b.

Another VBA script extracts the observation's height, wind direction and speed, data type, location, date and time from the reformatted data and creates charts containing the vertical profiles of wind speed and direction as shown in Figure 3. The data type, date and time of the observation are displayed in the upper left of the chart.

The AMU tested GUI VBA scripts at random times throughout the day to ensure the correct files were downloaded based on model initialization and availability times. There were occasions when the model data or observations were not available. Therefore, error checks were put into the scripts so the software would not fail but return an informative message to the user.

The 50 MHz profiler collects data from 8,000-60,000 ft while the 915 MHz profiler collects data from 400-10,000 ft. To provide a more-or-less continuous wind profile from these two instruments, a VBA script downloads, ingests and processes the 915 MHz profiler files in the same manner as for the 50 MHz profiler files. Due to the nature of the 915 MHz profilers, quality control parameters were added to the observations by finding and replacing missing data with data from the height immediately below the missing data. The replaced observation is changed to red text in the spreadsheet to highlight the changes for the LWOs. From the reformatted 915 MHz profiler observations, another VBA script creates wind speed and direction profiles and adds them to the existing 50 MHz profile charts as shown in Figure 4. The 915 MHz profiles are shown by the orange lines and the 50 MHz profiles are shown by the dark red lines.

🔀 🗈 😝 🖬 🖉 🐘 🛱 👫 🖓 💕 🖞 👔 👔 😓 🧮 😭 📔 LSP Upper-Level Winds alson - Microsoft Excel		医医管管室 网络	nn ca	🔐 📄 LSP Upper-	Level Windsalsm - Micro	soft Excel		
📕 📔 Home Insert Page Layout Formulas Data Resiew View Developer 🛩 🍘	- d ² × File Home	Insert Page La	out Formulas	Data Review	View Developer			× 🕜 = d ⁷ ×
Z180 • fr	 AF244 	• (*	8					~
A B C D E F G H		в с	D	E	F G	н	ן א נ	. <u>M</u> N
USE CAUTION: ENSURE DATA IS REASONABLE	2 1 L	Data: PROFIL	ER					
2 DATA MAY NOT BE CURRENT	2	ocation KSC						
3 (UPDATED ON 2012226 AT 17:02:35 GMT)	3	Date: 13 AUG	5 12					
a start data file number ==> 1	4 1	ime: 1655Z						
3 PS072261655	5	Height	(ft) Direction	n Speed (kts)				
6 2012226 1658	6	8	26	2 8.4				
PROFILE/SOUNDER DATA FROM PRIMARY WINDS SOURCE	7	<u>c</u>	222 25	9 7.8				
TEST NBR 02012	8	9	698 26	2 6.6				
9 PROFILER DATA	9	10	26	2 7.0				
20 KENNEDY SPACE CENTER, FL.	10	10	650 25	5 9.1				
1655Z 13 AUG 12	11	11	125 26	1 7.0				
12 ALT DIR SPD SHR WW S1 S2 S3 N1 N2 N3 WID1 WID2 WID3 G G QC	12	11	.601 25	8 9.5				
3	13	12	077 25	8 8.9				
GEOM DEG M/S /SEC M/S DB DB DB DB DB M/S M/S M/S 12 NN	14	12	552 26	1 9.9				
25	15	13	028 25	5 8.7				
2666 262 4.3 .000 -0.06123.7125.8115.9 63.3 62.7 51.8 0.4 0.4 0.66 0 0 0	16	13	504 24	1 8.0				
17	17	13	980 24	3 7.4				
2811 259 4.0.002 -0.31120.3122.0110.4 65.7 64.7 53.8 0.4 0.4 0.54 0 0 0	18	14	455 25	3 7.0				
25	19	14	931 25	7 6.2				
2956 262 3.4.004 -0.04116.3118.2111.7 67.3 66.1 57.1 0.4 0.4 0.52 0 0 0	20	15	407 25	5.6				
21	21	15	883 25	2 5.2				
3101 262 3.6 .001 -0.19120.9121.4109.3 64.4 63.3 52.4 0.4 0.3 0.58 0 0 0	22	16	358 24	7 4.9				
23	23	16	834 24	7 5.1				
3246 256 4.7.008 -0.06123.4118.3116.0 65.6 58.5 52.7 0.3 0.2 0.55 0 0 0	24	17	310 23	6.8				
25	25	17	785 23	9.5				
3391 264 3.6.008 -0.16119.6121.4117.3 58.8 58.6 50.5 0.4 0.3 0.56 0.0 0	26	18	261 24	0 10.5				
27	27	18	737 23	5 9.7				
3536 258 4.9.009 0.20122.6121.4113.2 60.8 58.5 51.3 0.3 0.4 0.50 0 0 0	28	19	213 22	5 8.2				
7	29	19	688 21	1 7.4				
3681 258 4,6.002 -0.04116.8120.4112.3 52.5 56.3 48.8 0.3 0,4 0.61 0 0 0	30	20	164 20	8.0				
31	31	20	640 20	7.4				
3826 261 5.1.004 0.15125.7124.9117.3 57.8 56.0 47.7 0.4 0.3 0.57 0 0 0	32	21	115 23	0 6.6				
3	33	21	591 24	5 6.4				
3971 256 4.5.005 0.16123.6117.9116.5 58.6 57.4 50.2 0.5 0.3 0.52 0 0 0	34	25	067 24	1 6.6				
35 _	35	22	543 24	0 6.4				
a 4116 241 4.1.008 0.09122.5116.9117.6 58.5 57.8 50.6 0.2 0.4 0.57 0 0 0	D	23	018 24	3 51				
THE CAR IN MAN INTE NAM / INTE RAP / INTE GFS / Fost NAM Prof / Fost RAP Prof / Fost GFS Prof / Fost NAM RADE / Fost RAP RADE / Fost GFS	I A Man	Int NAM / Int R	VP / Init GFS / R	st NAM Prof / Fcs	RAP Prof / Fost GFS	Prof / Fost NAM RAOB	Fost RAP RADE	Fost GFS Rild Labor
Ready Catculate 🔛 🛄 100% 🔿 🔻	C Ready Calculate	1 2 1						oni 🗢 🔹 🔿

Figure 2. a) Data from the 50 MHz profiler after being ingested into Excel and b) after unneeded parameters were removed, displaying the sensor type and location, date, time, height, wind direction and speed.



Figure 3. Wind speed (left) and wind direction (right) profiles at 1455 UTC 29 November 2012 from the 50 MHz wind profiler (dark red lines) plotted in Excel. Data type, date and time are shown in the upper left of the chart.



Figure 4. As in Figure 3 with the addition of the 1431 UTC 29 November 2012 915 MHz wind profiler (orange lines) plotted in Excel.

Another VBA script downloads, ingests and reformats the AMPS XMR radiosonde observations from the Spaceport Weather Data Archive. The AMPS files are also in ASCII format and are ingested into Excel as a text file. After downloading and ingesting the files, the VBA code removes all unneeded parameters and reformats the AMPS observations similar to the 50 MHz and 915 MHz profiler observations. From the reformatted data, another VBA script creates wind speed and direction profiles of AMPS and overlays them on the existing 50 MHz/915 MHz profile charts as shown in Figure 5. The AMPS profiles are shown by the green

lines and the 50 MHz profiles and 915 MHz profiles are as shown in Figure 4.

Additional VBA scripts download and process the model forecast point data from the Iowa State University server. The data files are in ASCII format and ingested into Excel as text files. Each script reformats the files and displays the tabular data to the user. From the reformatted data, the next VBA script creates wind speed and direction profiles of the model forecast point data and overlays the data on the 50 MHz profiler charts as shown in Figure 6.



Figure 5. As in Figure 4 with the addition of the 1115 UTC 29 November 2012 AMPS (green lines) plotted in Excel.



Figure 6. As in Figure 5 with the addition of the 1500 UTC 29 November 2012 RAP model 0-hour forecast (blue dashed lines) plotted in Excel.

2.2.2. Model Forecasts

Since the requirement is to provide the LWOs with a GUI to overlay model forecasts in 3-hour intervals from the current time through 12 hours, the AMU developed VBA scripts to display the forecast wind profiles up to 12 hours after the latest observation at each model's highest temporal resolution to assess the upper-level wind changes on day-of-launch for the launch directors. To keep the forecast charts uncluttered, the model forecast point data is overlaid on the AMPS and profiler observations on separate charts.

The VBA script that creates wind speed and direction profiles of the model forecast time intervals also overlays them on the AMPS observation profile

charts as shown in Figure 7. The AMPS observation (green lines) at 1115 UTC 29 November 2012 is plotted with the GFS model forecasts (blue dashed lines) based on the 0600 UTC 29 November 2012 model run valid from 1200 UTC 29 November 2012 to 0000 UTC 30 November 2012 in three-hour intervals. The model forecast profiles are always plotted in four different shades of blue ranging from light (first model forecast valid time) to dark (last model forecast valid time) making it easier for the user to discern between the model forecast valid times. The forecast profile colors match the colors of the text showing data type, date and time displayed on the chart. To unclutter the model forecast profiles, the LWO can right-click on any line and delete it from the chart.



Figure 7. Wind speed (left) and wind direction (right) profiles from the 1115 UTC 29 November 2012 AMPS observation (green lines) and GFS model forecasts (blue dashed lines) valid every three hours from 1200 UTC 29 November 2012 through 0000 UTC 30 November 2012 plotted in Excel. Data type, date and time are shown in the upper left of the chart.

The model forecast point data profiles can also be overlaid on the 50 MHz and 915 MHz profiler charts as shown in Figure 8. The 50 MHz profiler observation (dark red line) from 1754 UTC 27 November 2012 and the 915 MHz profiler observation from 1731 UTC 27 November 2012 are plotted with the NAM model forecasts (blue dashed lines) from the 1200 UTC 27 November 2012 model run and valid from 1800 UTC 27 November 2012 to 0300 UTC 28 November 2012 in three-hour intervals. Even though the NAM forecasts are available hourly, the forecasts valid every three hours are plotted on the chart to reduce clutter using the color scheme for model output described previously. To unclutter the model forecast profiles, the LWO can right-click on any line and delete it from the chart.



Figure 8. Wind speed (left) and wind direction (right) profiles from the 1754 UTC 27 November 2012 50 MHz profiler observation (dark red lines), 1731 UTC 27 November 2012 915 MHz profiler observation (orange lines) and NAM model forecasts (dashed blue lines) valid every three hours from 1800 UTC 27 November 2012 through 0300 UTC 28 November 2012 plotted in Excel. Data type, date and time are shown in the upper left of the chart.

3. GRAPHICAL USER INTERFACE

A single Excel workbook file serves as the GUI consisting of 25 tabs, or individual worksheets, that process and format the observations and model data as well as display tabular and graphic information. Within the Excel workbook are 21 modules containing the VBA scripts that control all aspects of the GUI operations based on user input.

3.1. User Interface

The AMU developed a menu on the Main tab in the Excel GUI as shown in Figure 9. Upon opening the Excel workbook file, the Main tab is displayed and VBA scripts automatically run to determine and display the date, local time, UTC time and the results of the test for DST (Eastern time since the tool will only be used in the Eastern Time zone) in the second row of the worksheet. There are three menus containing user-selectable model data and observations. The first menu, "*Initialize models*", is designed to allow the LWOs to compare each model's 0-hour forecast to the 50 MHz profiler, 915 MHz profiler and AMPS observations to determine

which model is most accurate. The second menu, "Compare Forecasts to Profiler Observations", allows the LWOs to compare each model's 12 hour forecasts in 3-hour time increments to the latest available 50 MHz and 915 MHz profiler observations. The third menu, "Compare Forecasts to RAOBS", allows the LWOs to compare each of the model's 12 hour forecasts in 3-hour time increments to the latest available AMPS observations.

In order to preserve the layout of the data and charts in each tab of the workbook, there are two buttons used to exit the GUI and Excel. The original file is never overwritten when the user chooses one of these buttons to exit. The button with green text will exit Excel and save a non-macro copy of the file in .xlsx format (Excel 2010) without any VBA code, but it will include all data and charts in the 25 tabs created during the session. It also automatically creates a filename for the saved file using the current date-time. A message box is then displayed to the LWO showing the filename and directory path to the file. The button with red text will exit Excel and will not save any version of the file.



Figure 9. Main tab of the Excel GUI shows the primary user interface for selecting model data and observations to display in the other tabs of the workbook.

3.2. Data Display

Multiple tabs were used to organize and process the textual and graphics data and displays. As shown in Figure 9, the tabs along the bottom of the workbook are color-coded to help users identify common displays or actions. The first nine tabs following the Main tab are color-coded to match the three colored menus on the Main tab. For example, the second light blue tab after the Main tab called "Fcst_RAP_Prof" corresponds to the light blue menu used to compare the RAP model forecasts to the profiler observations, while the third pink tab after the Main tab called "Fcst_GFS_RAOB" corresponds to the pink menu used to compare the GFS model forecasts to the AMPS observations. After the LWO makes a choice from a menu, the resulting charts are displayed in the tab corresponding to the menu color, model and observation type.

Textual observation and model data are stored in separate tabs based on the model data start time that

the observations will be compared to. This insures the observations are time-matched to each model. When an LWO chooses a model/observation pair from the menu, a VBA script automatically retrieves the observation and model data files from their respective servers, saves the raw data in the appropriate tabs, and then reformats the data to create charts and make the textual data easy for the LWO to read. An example of a reformatted textual observation data file from AMPS at 1500 UTC on 13 August 2012 is shown in Figure 10. Similarly, an example of a reformatted textual GFS model data file from the 1200 UTC 13 August 2012 model run is shown in Figure 11. Besides looking at the example charts shown in Figures 3-8 that are created from the reformatted text data, the LWO can inspect the observations and model data displayed in neatly organized Excel spreadsheets in formats they are familiar with.

Itel Note Note Portuge Add Note Vertuge Add/table Vertuge Add/table Vertuge Add/table Val -<	X 🗋 🞽	i 🖬 📕	🔊 🛍 🛍 🖞	📑 T ណំព	ι 📴 🚍 🔐	Ŧ	LSP	Upper-Level V	Vinds.xlsm	- Microsof	t Excel							• X
V3 V	File	Home	Insert Pa	ge Layout F	Formulas Data	Review		Developer	Add-Ir								× ?	
A B C D E F G H J X L M N O P Sensor: AMP/LR	Y	/63	- (c	f_{κ}														
1 Service AMP/LR Image: CAFS	A 1	A	В	С	D	E	F	G	н	1	J	к	L	м	N	0	Р	Q
2 CACK Index Index<	1 Sens	or:	AMP/LR															
13 AUG 1 Image: 13 AUG 2 Image:	2 Loca	tion:	CCAFS															
Imme 15002 Impe 15002 Specified Impe Impe<	3 Date	:	13 AUG 12															
Height (H) Direction Speed (kts) Note of the second	4 Time	e:	1500Z															
6 16 220 7.0	5		Height (ft)	Direction	Speed (kts)													
7 1000 215 9.7	6		16	220	7.0													
8 2000 222 9.6	7		1000	215	9.7													
9 3000 238 10.7 10	8		2000	222	9.6													
10 4000 232 14.1 1	9		3000	238	10.7													
11 5000 239 13.8 <t< th=""><th>10</th><th></th><th>4000</th><th>232</th><th>14.1</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></t<>	10		4000	232	14.1													
12 6000 236 13.2 13 7000 227 11.3 11.1 14 8000 240 13.9 11.1 15 9000 242 15.0 11.1 16 10000 238 14.9 11.1 17 11000 233 17.2 11.1 18 12000 233 23.7 11.1 11.1 19 13000 227 24.3 11.1 11	11		5000	239	13.8													
13 7000 227 11.5 <	12		6000	236	13.2													
10 8000 240 13.9 13 9000 242 15.0 1000 14 1000 238 14.9 1000 15 12000 233 23.7 1000 16 12000 233 23.7 1000 16 12000 243 23.7 1000 16 13000 247 24.3 1000 16 14000 241 20.6 1000 17 15000 243 14.9 1000 18 15000 243 14.9 1000 18 16000 243 14.9 1000 18 19000 185 8.5 1000 19 1000 177 5.8 1000 10 22000 177 5.8 1000 10 22000 145 2.2 1000 10 24000 41 11.2 1000 10 24000 41 11.2 1000 10 26000 50 8.3	13		7000	227	11.5													
1000 242 15.0 1000 238 14.9 1000 1000 238 14.9 1000 <t< th=""><th>14</th><th></th><th>8000</th><th>240</th><th>13.9</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></t<>	14		8000	240	13.9													
1000 238 14.9 1000 238 14.9 1000 1000 235 17.2 1000 233 23.7 1000 1000 233 23.7 1000 1000 243 23.7 1000 1000 241 20.6 1000 1000 241 20.6 1000 1000 248 19.0 1000	15		9000	242	15.0													
11000 235 17.2 11000 235 17.2 11000 233 23.7 11000 227 24.3 11000 241 20.6 11000 241 20.6 11000 243 14.9 11000 243 14.9 11000 243 14.9 11000 243 14.9 11000 243 14.9 11000 243 14.9 11000 243 14.9 11000 243 14.9 11000 115 8.5 11000 115 2.2 11000 115 2.2 11100 110 11100 11.2 11100 11.2	16		10000	238	14.9													
12000 233 23.7 12000 227 24.3 13000 227 24.3 14000 241 20.6 15000 248 19.0 15000 243 14.9 16000 243 14.9 17000 243 14.9 18000 224 9.9 19000 185 8.5 19000 185 8.5 19000 195 2.9 19000 195 2.9 19000 195 2.9 19000 195 2.9 19000 195 2.9 19000 195 2.9 19000 195 2.9 19000 195 2.9 19000 195 2.9 19000 195 2.9 19000 195 2.9 19000 10 2.9 19000 10 1.2 19000 10 1.2 19000 10 1.2 19000 10 1.9 19000 10 1.9 19000 10 1.9 19000 10 1.9 <t< th=""><th>17</th><th></th><th>11000</th><th>235</th><th>17.2</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></t<>	17		11000	235	17.2													
1300 227 24.3 14000 241 20.6 15000 248 19.0 15000 243 14.9 17000 243 12.2 18000 224 9.9 19000 185 8.5 19000 185 8.5 20000 177 5.8 212 20000 175 22 20000 145 23 22000 145 24 9.9 25 19000 185 26 20000 177 5.8 9.9 21000 195 22000 145 22000 14 11.2 23000 8 24000 41 11.2 25000 50	18		12000	233	23.7													
1400 241 20.6 1500 248 19.0 16000 243 14.9 17000 243 12.2 18000 224 9.9 19000 185 8.5 19000 185 8.5 20000 177 5.8 212000 145 2.2 223000 145 2.2 234 22000 145 245 22000 145 25 2000 145 26 22000 145 27 23000 8 30 24000 41 31 25000 50	19		13000	227	24.3													
1 1500 248 19.0 2 1600 243 14.9 14.9 2 1600 243 14.9 14.9 2 17000 243 12.2 14.9 2 1800 224 9.9 14.9 25 19000 185 8.5 14.9 26 2000 177 5.8 14.9 27 21000 195 2.9 14.9 26 2000 145 2.2 14.9 27 23000 8 6.0 14.9 26 26000 50 8.3 14.9	20		14000	241	20.6													
1600 243 14.9 1700 243 14.9 1800 224 9.9 1900 185 8.5 2000 177 5.8 2000 177 5.8 21000 195 2.9 22000 145 2.2 23000 8 6.0 24000 41 11.2 25 26000 50	21		15000	248	19.0													
1700 243 12.2 1800 224 9.9 19000 185 8.5 20000 177 5.8 27 21000 195 20000 145 2.2 20000 145 2.2 20000 145 2.2 20000 141 11.2 20000 50 8.3	22		16000	243	14.9													
1800 224 9.9 1800 124 9.9 1900 185 8.5 20000 177 5.8 21000 195 2.9 22000 145 2.2 22000 145 2.2 23000 8 6.0 24 25000 10.3 25 26000 50	23		17000	243	12.2													
1900 185 8.5 2000 177 5.8 7 2100 195 2.9 22000 145 2.2 12 23000 8 24000 41 11.2 12 25000 50 25 26000 50	24		18000	224	9.9													
1000 177 5.8 177 2.9 1.9 18 2.2000 195 19 2.3000 8 10 2.4000 41 11.2 2.6000 50	25		19000	185	8.5													
27 21000 195 2.9 82 22000 145 2.2 92 23000 8 6.0 93 24000 41 11.2 94 25000 38 10.3 95 26000 50 8.3	26		20000	177	5.8													
22000 145 2.2 23000 8 6.0 24000 41 11.2 2500 2500 50 22000 50 8.3	27		21000	195	2.9													
19 23000 8 6.0 30 24000 41 11.2 31 25000 38 10.3 32 26000 50 8.3	28		22000	145	2.2													
24000 41 11.2 31 25000 38 10.3 32 26000 50 8.3	29		23000	8	6.0													
31 25000 38 10.3 32 26000 50 8.3	30		24000	41	11.2													
22 26000 50 8.3	31		25000	38	10.3													
A NAM OF DAOD NAM TO MUS (DAD TO MUS (DAD TO MUS) DAOD NAM (DA	32	0.000	26000	50	8.3	C 50 MU	/ HA14 . A	E MUL	10.015	MIL (17	C OIE MIT	10400		00.040	DAOD CTC			
	Ready	<u></u>		<u>ou_mn2 / K</u> /	HP_DU_MHZ / GP	5_30_MHZ	C WAM_9		GAP_915_		5_913_MHZ	Z RAUB_	RAM Z RA	OB_KAP		100%		•

Figure 10. AMPS data after being ingested into Excel and reformatted displaying the sensor type and location, date, time, height, wind direction and speed.

	🔊 🔍 🛍 🕺	📑 🕈 🖬 🕅	$ \mathbf{r} = \mathbf{C} \subseteq \mathbf{\Omega} $	Ŧ	LSP Upper-Level V	/inds.xlsm - Mi	crosoft Excel					•
le Home	Insert Pa	ge Layout 🛛 🕯	Formulas Data	Review Vie	w Developer	Add-Ins					× ?	-
AG63	- (C	f _×	D	с с	G	ч		V		M	N	
A Model:	GES	C C	U	Model	GES	n		Model	GES	IVI	N	
ocation:	74794			Location:	74794			Location:	74794			
Date:	13 AUG 12			Date:	13 AUG 12			Date:	13 AUG 12			
Time:	1200Z			Time:	1500Z			Time:	1800Z			
	Height (ft)	Direction	Speed (kts)		Height (ft)	Direction	Speed (kts)		Height (ft)	Direction	Speed (kts)	
	90	214	6.3		90	223	4.3		88	167	5.4	
	256	213	6.5		254	225	4.4		255	170	5.5	
	443	213	6.5		444	225	4.7		444	174	5.5	
	659	212	6.6		659	227	4.8		663	178	5.4	
	900	212	7.1		904	228	5.2		907	192	5.6	
	1179	210	7.7		1180	229	5.7		1185	205	6.0	
	1492	210	8.5		1494	231	6.5		1501	217	6.8	
	1847	212	9.6		1850	235	7.4		1858	226	7.6	
	2245	216	10.6		2249	239	8.2		2259	233	8.3	
	2697	220	11.4		2701	242	9.2		2714	237	9.3	
	3205	223	12.2		3210	245	10.3		3221	241	10.2	
	3774	224	13.1		3777	246	11.1		3793	244	11.0	
	4412	224	13.9		4414	246	11.7		4432	245	12.0	
	5124	225	14.6		5127	243	12.3		5142	245	13.3	
	5916	226	14.8		5916	240	12.8		5933	243	14.2	
	6792	229	15.2		6793	237	13.4		6809	242	14.9	
	7759	232	15.6		7757	235	14.4		7779	241	16.3	
	8821	232	16.9		8820	232	16.5		8840	240	18.0	
	9982	229	18.7		9978	230	19.2		10000	239	20.1	
	11246	229	20.7		11240	230	21.8		11263	239	22.1	
	12612	231	21.8		12608	231	23.6		12633	237	23.5	
	14082	235	20.9		14076	232	22.7		14103	235	22.9	
	15658	238	16.0		15653	234	16.7		15678	238	18.3	
	17341	238	10.3		17333	235	9.9		17361	242	11.6	
	19129	197	2.0		19123	189	2.6		19155	231	4.0	
	21026	73	4.1		21015	87	3.5		21046	45	1.1	
	23013	28	4.6		23004	15	6.0		23038	17	6.5	

Figure 11. GFS model three-hour forecast data after being ingested into Excel and reformatted displaying the model type and location, date, time, height, wind direction and speed for each three-hour forecast interval.

4. SUMMARY AND FUTURE WORK

The LWOs requested the AMU develop a capability in the form of a GUI that would allow them to plot upperlevel wind speed and direction observations and then overlay point forecast profiles from the NCEP NAM, RAP and GFS models to assess the performance of these models. The AMU developed an Excel-based GUI for the LWOs to rapidly assess the model forecast of upper-level winds by comparing them to the CCAFS AMPS rawinsondes and the KSC 50 MHz and 915 MHz wind profilers and provide that information to the launch directors and other decision makers. The GUI allows the LWOs to first initialize the models by comparing the 0-hour model forecasts to the observations and determine which model has the best performance. The LWOs can then display the desired model forecasts in 3-hour intervals from the current time through 12 hours.

The AMU wrote Excel VBA scripts that drive the GUI by automatically acquiring, downloading and processing the observations and model point forecast data, and then displaying the resulting output in text format in Excel spreadsheets and in graphic format as

Excel charts. The output of the observational data provides the LWO with the observation type and location, date and time, height, and wind direction and speed. The output of the model data provides the LWO with the model name and forecast point location, date and time of the model start and forecast intervals, height, and wind direction and speed.

In the future, the AMU would like to add wind profile forecasts from a local high resolution version of the Weather Research and Forecasting (WRF) model. The AMU is working on a task to assess and implement a high temporal and horizontal resolution WRF to be run locally. The intent of this task is to determine the optimum physics schemes and data assimilation methods to run WRF over east-central Florida on a routine basis. Once WRF is running routinely, the WRF forecasts could be added to this tool and used in the same manner as the NCEP NAM, RAP and GFS model forecasts.

The final report for this work is available on the AMU website at <u>http://science.ksc.nasa.gov/amu</u>.

NOTICE

Mention of a copyrighted, trademarked, or proprietary product, service, or document does not constitute endorsement thereof by the author, ENSCO, Inc., the AMU, the National Aeronautics and Space Administration, or the United States Government. Any such mention is solely for the purpose of fully informing the reader of the resources used to conduct the work reported herein.